



**Product Number:** 51833

**Order Abbreviation:** QTP 2X26/CF/UNV DM

**General Description:** LOW POWER DUAL ENTRY BALLAST.

#### Product Information

|                                   |                          |
|-----------------------------------|--------------------------|
| Abbrev. With Packaging Info.      | QTP2X26CFUNV 20/CS 1/SKU |
| Ballast Factor                    | 1                        |
| Ballast Height H (in)             | 1.0630                   |
| Ballast Length L (in)             | 4.9450                   |
| Ballast Width W (in)              | 2.4020                   |
| Circuit Type                      | SERIES                   |
| Input Current (Amps)              | 0.00                     |
| Nominal Voltage (V)               | 120.00                   |
| Nominal Voltage (V)               | 120-277V                 |
| Number of Lamps                   | 2                        |
| Power Factor                      | >0.98                    |
| Primary Lamp Type                 | 26W DD/E,T/E             |
| Sound Rating                      | A                        |
| Starting Method                   | PROGRAMMED RAPID START   |
| Starting Temperature - Fahrenheit | -5                       |
| Starting Temperature - Celsius    | -20                      |
| Total Harmonic Distortion (THD)   | <10%                     |
| Wiring Method                     | PLUG-IN CONNECTORS       |
| Total Maximum Wattage             | 61                       |
| Language Strategy                 | 1                        |

#### Footnotes

- Remote Mounting up to 15 feet for one lamp and up to 6 feet for two lamps
- 70C Max Case Temperature
- 75C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Class A Sound Rating
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: -4F/-20C.
- ANSI C62.41 cat. B3 Transient Protection.