

# 22910 - F15T8/AR/FS 6PK

## GE plant and aquarium 15 watt T8 1-pack

• 1.0 inch diameter T8 with medium bi-pin (g13) base

- 18 inches long
- · Lasts 3.4 years based on 6 hours per day usage

• Contains a combination of phosphors that produce light rich in reds and blues, specially designed to promote the growth and flowering of plants and aquatic vegetation

• GE plant and aquarium fluorescent bulbs highlight the natural beauty and color of aquatic life and plants. They are specially designed to promote growth and flowering of plants and aquatic vegetation

• Use to highlight the natural beauty and color of aquatic life and plants



4		
---	--	--

#### **CAUTIONS & WARNINGS**

#### Caution

Lamp may shatter and cause injury if broken

- Do not use excessive force when installing lamp.

- Wear safety glasses and gloves when handling lamp.

#### Warning


Risk of Electric Shock

- Avoid direct water/liquid contact.

- Turn power off before inspection, installation or removal.

### **GRAPHS & CHARTS**

Graphs\_Lamp Mortality



**Graphs\_Spectral Power Distribution** 

### **GENERAL CHARACTERISTICS**

Lamp Type

Bulb Base Rated Life (NOM) Rated Life (instant start) @ Time **Bulb Material** Starting Temperature (MIN) Mercury Content (NOM) Picograms of Mercury (NOM) **Primary Application** 

Linear Fluorescent - Straight Linear **T**8 Medium Bi-Pin (G13) 7500.0 h 7500 h @ 3 h

Soda lime 10.0 °C 18.0 mg 3555.6 pg Saltwater Aquarium47;Freshwater Aquarium47;Speciality

#### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 675.0 Nominal Initial Lumens per Watt 45.0 (NOM) Color Temperature (NOM) Color Rendering Index (CRI) (NOM)

9325.0 K 64.0

### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	15.0
Open Circuit Voltage (rapid	220.0 V
start) (MAX)	
Open Circuit Voltage (rapid	157 V @ 10 °C
start) Min @ Temperature	
Cathode Resistance Ratio - Rh/	6.5
Rc (MAX)	
Preheat Voltage (MIN)	4.25 V

### DIMENSIONS

Maximum Overall Length (MOL) (NOM) Nominal Length (NOM) Bulb Diameter (DIA) (MAX) Bulb Diameter (DIA) (NOM)

18.000 in(457.2 mm) 18.000 in(457.2 mm) 1.100 in(27.9 mm) 1.000 in(25.4 mm)

### **PRODUCT INFORMATION**

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

22910 F15T8/AR/FS 6PK BUNDLE 30043168229105 24 Unit 1 24

043168229104

