





GE
Lighting

26683 - ARC250T/H960/E39

GE Multi-Vapor® Arcstream® Quartz Metal Halide T15

- Compact size, white light, excellent color Precise optical control delivers a concentrated beam of light right where it's needed



CAUTIONS & WARNINGS

R- WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured, and the arc tube continues to operate. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain types of lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Visit the FDA website for more information: <http://www.fda.gov/cdrh/radhealth/products/urburns.html>

Caution

- Lamp may shatter and cause injury if broken
 - Dispose of lamp in a closed container.
 - Do not use excessive force when installing lamp.
 - Do not use lamp if outer glass is scratched or broken.
 - Wear safety glasses and gloves when handling lamp.

Warning

- A damaged lamp emits UV radiation which may cause eye/skin injury
 - Turn power off if glass bulb is broken. Remove and dispose of lamp.
- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- Risk of Electric Shock
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Turn power off before inspection, installation or removal.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.
- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Operate lamp only in specified position.
 - Turn lamp off at least once for 15 minutes per week.
 - Use in enclosed fixture rated for this product.
 - Use only properly rated ballast.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution

GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Quartz Metal Halide
Bulb	T15
Base	Mogul Screw (E39)
Bulb Finish	Clear
Rated Life (NOM)	10000.0 h
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Enclosed fixtures only
Mercury Content (NOM)	13.5 mg
Picograms of Mercury (NOM)	101.5 pg

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	19000.0
Mean Lumens (NOM)	13300.0
Nominal Initial Lumens per Watt (NOM)	76.0
Color Temperature (NOM)	6000.0 K
Color Rendering Index (CRI) (NOM)	90.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	250.0
Burn Position	Horizontal ±15°
Warm Up Time to 90% (MAX)	5.0 min
Warm Up Time to 90% (NOM)	2.0 min
Hot Restart Time to 90% (MIN)	10.0 min
Hot Restart Time to 90% (MAX)	15.0 min

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	8.370 in(212.6 mm)
Nominal Length (NOM)	8.370 in(212.6 mm)
Bulb Diameter (DIA) (NOM)	1.875 in(47.6 mm)
Light Center Length (LCL) (NOM)	5.620 in(142.7 mm)

PRODUCT INFORMATION

Product Code	26683
Description	ARC250T/H960/E39
ANSI Code	M80
Standard Package	Case
Standard Package GTIN	10043168266830
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168266833

