

**Product** 64588**Number:****Order** MP50/C/U/MED**Abbreviation:**

**General** 50W METALARC PRO-TECH PULSE START quartz metal halide  
**Description:** lamp, reduced color shift, MED base, E17 bulb, open fixture rated, universal burn, coated, 2900K

### Product Information

Abbrev. With Packaging Info.	MP50CUMED 20/CS 1/SKU
ANSI Code	M 110/O
Approx. Lumens (initial - horizontal)	3000
Approx. Lumens (initial - vertical)	3000
Approx. Lumens (mean - horizontal)	1350
Approx. Lumens (mean - vertical)	1350
Arc Length (in)	0.31
Arc Length (mm)	8
Average Rated Life - Horizontal (hr)	10000
Average Rated Life - (hr)	10000
Average Rated Life - Vertical (hr)	20000
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	2900
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	5-7
Lamp Finish	Coated
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	85.00
Nominal Wattage (W)	50.00

Operating Position	Universal
Warm-up Time (min)	2-4

**Footnotes**

- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.