



Product 54032

Number:

Order 64621 HLX

Abbreviation:

General 100 watt, tungsten halogen, low voltage without reflector
Description:

Product Information

Abbrev. With Packaging Info.	64621HLX 12V 30/CS 1/SKU
Application	AIRCRAFT, FIBER-OPTIC, MICROSCOPE
Average Rated Life (hr)	2000
Base	PG22
Bulb	T11,5
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3300
Diameter d (in)	0.472
Diameter d (mm)	12.00
Distance a (in)	0.702
Distance a (mm)	18
Family Brand Name	XENOPHOT® (HLX)
Filament Dimensions Length (in)	0.105
Filament Dimensions Length (mm)	2.7
Filament Dimensions Width (in)	0.183
Filament Dimensions Width (mm)	4.7
Lamp Finish	Clear
Length l (in)	1.872
Length l (mm)	48
Length l max. (in)	1.872
Length l max. (mm)	48
Light Center Length - LCL (in)	0.702
Light Center Length - LCL (mm)	18
Luminous Flux (lm)	2880
Maximum Overall Length - MOL (in)	1.872
Maximum Overall Length - MOL (mm)	48
Nominal Voltage (V)	12.00
Nominal Wattage (W)	100.00
Operating Position	s 90

Type of Current

AC

Footnotes

- s (Operating Position) = Vertical, base down