

**Product** 67508**Number:****Order** LU150/55/MED**Abbreviation:****General** 150W LUMALUX high pressure sodium HID lamp, E26**Description:** based, E17 bulb, universal burn, clear, 2100K

Product Information

Abbrev. With Packaging Info.	LU15055MED 20/CS 1/SKU
ANSI Code	S55
Approx. Lumens (initial - horizontal)	15800
Approx. Lumens (initial - vertical)	15800
Approx. Lumens (mean - horizontal)	13400
Approx. Lumens (mean - vertical)	13400
Arc Length (in)	1.54
Arc Length (mm)	39
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Avg Rated Life (hrs)	24000+
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Lumalux®
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	3.7
Light Center Length - LCL (mm)	93
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.71
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	55.00
Nominal Wattage (W)	150.00

Operating Position

Universal

Warm-up Time (min)

3-4 MINUTES

Footnotes

- Use with 4000V pulse rated sockets only.
- 55 Volt lamp.
- Mean lumens measured at 50% of average rated life
- LU150/100 and LU150/55 lamps are not interchangeable.