

**Product** 64321**Number:****Order** M400/PS/U**Abbreviation:**

General 400W METALARC PULSE START metal halide lamp, reduced
Description: color shift, E39 base, BT37 bulb, enclosed fixture rated,
 universal burn, clear, 4000K

*** Full Case Required****Product Information**

Abbrev. With Packaging Info.	M400PSU 6/CS 1/SKU
ANSI Code	M155/E
ANSI Code 2	M135/O
Approx. Lumens (initial - horizontal)	31000
Approx. Lumens (initial - vertical)	36000
Approx. Lumens (mean - horizontal)	22400
Approx. Lumens (mean - vertical)	25500
Arc Length (in)	1.5
Arc Length (mm)	38
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	BT37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Wattage (W)	400.00

6/23/2014

Product Details

Operating Position

Universal

Warm-up Time (min)

2-4