

**Product** 64774**Number:****Order** MP175/C/BU-ONLY**Abbreviation:****General** 175W METALARC PRO-TECH quartz metal halide lamp,**Description:** EX39 base, BT28 bulb, open fixture rated, base up only, clear, 3800K**Product Information**

| | |
|---------------------------------------|---------------------------|
| Abbrev. With Packaging Info. | MP175CUBUONLY 6/CS 1/SKU |
| ANSI Code | M57/O |
| Approx. Lumens (initial - vertical) | 12800 |
| Approx. Lumens (mean - vertical) | 7800 |
| Average Rated Life - Vertical (hr) | 10000 |
| Base | EX39 Exclusionary Mogul |
| Bulb | BT28 |
| Color Rendering Index (CRI) | 70 |
| Color Temperature/CCT (K) | 3800 |
| Diameter (in) | 3.504 |
| Diameter (mm) | 89.00 |
| Family Brand Name | Metalarc Pro-Tech® |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 7-12 |
| Lamp Finish | Coated |
| Light Center Length - LCL (in) | 5 |
| Light Center Length - LCL (mm) | 127 |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 8.31 |
| Maximum Overall Length - MOL (mm) | 211 |
| Nominal Voltage (V) | 132.00 |
| Nominal Wattage (W) | 175.00 |
| Operating Position | Base up within 15deg only |
| Warm-up Time (min) | 2-4 |

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.

