

**Product** 64840**Number:****Order** MCP50/U/MED/830 PB**Abbreviation:****General Description:** 50W high CRI, reduced color shift, high performance, open fixture rated metal halide lamp, ceramic arc tube, clear, universal burn**Product Information**

Abbrev. With Packaging Info.	MCP50UMED830 PB 85V 12/CS 1/SKU
ANSI Code	C110/O,C148/O
ANSI Code 2	C110/O, C148/O
Approx. Lumens (initial - horizontal)	4100
Approx. Lumens (initial - vertical)	4100
Approx. Lumens (mean - horizontal)	2850
Approx. Lumens (mean - vertical)	2850
Arc Length (in)	0.25
Arc Length (mm)	6.3
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Avg Rated Life (hrs)	12000
Base	E26 Medium
Bulb	ED17
Color Rendering Index (CRI)	88
Color Temperature/CCT (K)	3000
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Metalarc® Powerball
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Clear
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	90.00

Nominal Wattage (W)	50.00
Operating Position	Universal
Warm-up Time (min)	2-4



Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.