

**Product** 64738**Number:****Order** MSP360/C/SS/BU-ONLY**Abbreviation:**

General 360W METALARC PRO-TECH SUPERSAVER energy saving
Description: quartz metal halide lamp, high output, position dedicated, EX39 base, BT37 bulb, open fixture rated, coated, base up only, 3600K

Product Information

Abbrev. With Packaging Info.	MSP360CSSBUONLY 6/CS 1/SKU
ANSI Code	M59/O:M165/O
Approx. Lumens (initial - vertical)	34000
Approx. Lumens (mean - vertical)	16300
Average Rated Life - Vertical (hr)	20000
Base	EX39 Exclusionary Mogul
Bulb	BT37
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3600
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc® Super Saver
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Coated
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	120.00
Nominal Wattage (W)	360.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Footnotes

- Operates at 360 watts on 400w M59 ballast or a M165 ballast.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries.

See lamp warning.