



GE
Lighting

26152 - 306

GE S8 - Aircraft; Low Voltage

Photo
Not Available



GENERAL CHARACTERISTICS

Lamp Type	Miniature - S Shape
Bulb	S8
Base	Double Contact Bayonet (BA15d)
Filament	C-2V
Rated Life (MIN)	14.0 h
Rated Life (Vert)	300.0 h
Rated Life (NOM)	300.0 h
Rated Life (Hor)	14.0 h
Bulb Material	Lead glass
Atmosphere	Gas-filled
Primary Application	Aircraft;Low Voltage

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	188.0
Initial Lumens (NOM)	188.0
Initial Lumens (Hor)	13.42857
Nominal Initial Lumens per Watt (NOM)	13.42857
Center Beam Candlepower (CBCP) (NOM)	188.0
Mean Spherical Candlepower (MSCP) (NOM)	15.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	14.0
Voltage (MIN)	300.0
Voltage (NOM)	28.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	2.000 in(50.8 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)
Light Center Length (LCL) (NOM)	1.120 in(28.4 mm)

PRODUCT INFORMATION

Product Code	26152
Description	306
ANSI Code	306
Standard Package	Case
Standard Package GTIN	20043168261528
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168261524

NOTES

- Filament: Supported