




GE  
Lighting

**39904 - 1229**

GE S8 - Low Voltage; Emergency Building; Emergency Building Light

Photo  
Not Available



**GENERAL CHARACTERISTICS**

Lamp Type	Miniature - S Shape
Bulb	S8
Base	Double Contact Bayonet (BA15d)
Filament	C-2V
Rated Life (NOM)	400.0 h
Atmosphere	Gas-filled
Primary Application	Emergency Building;Low Voltage

**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)	188.0
Nominal Initial Lumens per Watt (NOM)	12.53333
Mean Spherical Candlepower (MSCP) (NOM)	15.0

**ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	15.0
Voltage (NOM)	40.0

**DIMENSIONS**

Maximum Overall Length (MOL) (NOM)	2.000 in(50.8 mm)
Bulb Diameter (DIA) (NOM)	1.000 in(25.4 mm)
Light Center Length (LCL) (NOM)	1.120 in(28.4 mm)

**PRODUCT INFORMATION**

Product Code	39904
Description	1229
ANSI Code	1229
Standard Package	Case
Standard Package GTIN	20043168399047
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168399043

**NOTES**

- Filament: Supported