





GE
Lighting

44840 - 782

GE T2.75 (T2 3/4) - Emergency Building



CAUTIONS & WARNINGS

Caution

- Risk of Burn
 - Allow lamp/fixture to cool before handling.

Warning

- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
 - Avoid direct water/liquid contact.
 - Dispose of lamp in a closed container.
 - Do not exceed rated voltage.
 - Do not turn on lamp until fully installed.
 - Do not use lamp if outer glass is scratched or broken.
 - Keep children away.
 - Use eye protection when handling lamp.
 - Use in enclosed fixture rated for this product.
 - Use protective screen when handling.

NOTES

- .028" metal pins spaced 44mm (.157") apart. GE's two-pin lamps might not be compatible with all G-4 sockets since many sockets do not provide clearance for the exhaust tip.

GENERAL CHARACTERISTICS

Lamp Type	Miniature - T & TL Shape
Bulb	T2.75 (T2 3/4)
Base	2-Pin (G4)
Filament	C-6
Rated Life (NOM)	2000.0 h
Bulb Material	Hard glass
Atmosphere	Gas-filled
Primary Application	Emergency Building

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	314.0
Nominal Initial Lumens per Watt (NOM)	15.7
Mean Spherical Candlepower (MSCP) (NOM)	25.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	20.0
Voltage (NOM)	12.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	1.050 in(26.7 mm)
Bulb Diameter (DIA) (NOM)	0.344 in(8.7 mm)
Light Center Length (LCL) (NOM)	0.770 in(19.6 mm)

PRODUCT INFORMATION

Product Code	44840
Description	782
ANSI Code	782
Standard Package	Case
Standard Package GTIN	20043168448400
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168448406