



**Product Number:** 54102

**Order Abbreviation:** HSR 400/60

**General Description:** 400 watt, metal halide, single-ended, no hot restart

### Product Information

Abbrev. With Packaging Info.	HSR40060 67V 10/CS 1/SKU
Application	Entertainment, Effect and Architectural Lighting
Average Luminance (cd/cm <sup>2</sup> )	20000
Average Rated Life (hr)	1000
Base	GX9.5 Bipin Prefocus
Bulb	T21
Class	C (gas)
Color Rendering Index (CRI)	85
Color Temperature (K)	6000
Cooling	Convection
Current (A)	6.9
Diameter d (in)	0.906
Diameter d (mm)	23.00
Distance a (mm)	62
Electrode Gap (cold) (mm)	5
Family Brand Name	HSR®
Hot Restart	No
Lamp Finish	Clear
Length l (mm)	110
Light Center Length - LCL (mm)	62
Luminous Flux (lm)	33000
Maximum Base Temperature °C	230
Maximum Overall Length - MOL (mm)	110
Nominal Voltage (V)	67.00
Nominal Wattage (W)	400.00
Operating Position	Any
Reflector Coating	23.00
Type of Current	AC

### Footnotes

- Type of current: sine-wave (sinusoidal) AC.