



**Product Number:** 58851

**Order Abbreviation:** 6.6A/200T4Q/2PPF/58750/EZL/DL

**General Description:** 200 WATT, TUNGSTEN HALOGEN, CURRENT CONTROLLED, SINGLED-END, BI-PIN, AIRFILED LONG LIFE

#### Product Information

Abbrev. With Packaging Info.	6.6A200T4Q2PPF58750EZLDL 12/CS 1/SKU
ANSI Code	EZL
Application	Airfield/Airport
Average Rated Life (hr)	1300
Base	GY9.5 BIPIN
Bulb	T13
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	100
Current (A)	6.6
Diameter d (in)	0.512
Diameter d (mm)	13.00
Filament	CC-6
Filament Dimensions Length (in)	.149
Filament Dimensions Length (mm)	3.8
Filament Dimensions Width (in)	.216
Filament Dimensions Width (mm)	5.5
Lamp Finish	Clear
Light Center Length - LCL (in)	1.54
Light Center Length - LCL (mm)	39.1
Maximum Overall Length - MOL (in)	2.56
Maximum Overall Length - MOL (mm)	65
Nominal Wattage (W)	200.00
Operating Position	Any
Type of Current	AC

#### Footnotes

- This lamp type is twice the life of the ANSI standard version.

