



Product Number: 58652

Order Abbreviation: 5T3Q/CL 12V

General Description: Tungsten Halogen Quartz Bi-Pin STANDARD Low Pressure Clear Finish UV-Filter With Transverse Filament G4 Bi-Pin Base 5Watt 12Volt 2000Hr Lamp Life

Product Information

Abbrev. With Packaging Info.	5T3QCL 12V 40/CS 1/SKU
Approx. Lumens	60
Average Rated Life (hr)	4000
Base	G4 Bipin
Bulb	T3
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	0.375
Diameter (mm)	9.53
Ecologic	YES
Family Brand Name	STANDARD Bi-Pin
Filament	TRANSVERSE
Lamp Finish	Clear
Light Center Length - LCL (in)	0.875
Light Center Length - LCL (mm)	22.225
Maximum Overall Length - MOL (in)	1.250
Maximum Overall Length - MOL (mm)	31.75
Nominal Voltage (V)	12.00
Nominal Wattage (W)	5.00

Footnotes

- For use where seal temperature does not exceed 650F.
- Standard Clear - UV Filter Quartz
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.