



Product Number: 58661

Order Abbreviation: 20T3Q/CL 12V

General Description: Tungsten Halogen Quartz Bi-Pin STANDARD Low Pressure Clear Finish UV-Filter With Transverse Filament G4 Bi-Pin Base 20Watt 12Volt 2000Hr Lamp Life

Product Information

Abbrev. With Packaging Info.	20T3QCL 12V 40/CS 1/SKU
Approx. Lumens	320
Average Rated Life (hr)	2000
Base	G4 Bipin
Bulb	T3
Centerbeam Candlepower (cp)	369
Class	F (GAS)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	21.654
Diameter (mm)	550.00
Ecologic	YES
Family Brand Name	STANDARD Bi-Pin
Filament	CC-8
Horizontal Beam Angle (deg)	95
Lamp Finish	Clear
Light Center Length - LCL (in)	44
Light Center Length - LCL (mm)	95
Maximum Overall Length - MOL (in)	3 1/25
Maximum Overall Length - MOL (mm)	885
Nominal Voltage (V)	12.00
Nominal Wattage (W)	20.00
Vertical Beam Angle (deg)	999

Footnotes

- For use where seal temperature does not exceed 650F.
- Standard Clear - UV Filter Quartz
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

