



Product Number: 58676

Order Abbreviation: 50T4Q/CL/AX 12V

General Description: Tungsten Halogen Quartz Bi-Pin STARLITE Low Pressure Clear Finish UV-Filter With Axial Filament GY6.35 Bi-Pin Base 50Watt 12Volt 4000Hr Lamp Life

Product Information

Abbrev. With Packaging Info.	50T4QCLAX 12V 40/CS 1/SKU
Approx. Lumens	900
Average Rated Life (hr)	4000
Base	GY6.35 Bipin
Bulb	T12
Centerbeam Candlepower (cp)	700.00
Class	G (GAS)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	0.472
Diameter (mm)	12.00
Ecologic	YES
Family Brand Name	STARLITE® Bi-Pin
Filament	CC-8
Horizontal Beam Angle (deg)	95
Lamp Finish	Clear
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	50.00
Vertical Beam Angle (deg)	258

Footnotes

- Starlite Low Pressure - UV Filter Quartz
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.