



**Product Number:** 58680

**Order Abbreviation:** 75T4Q/CL/AX 12V

**General Description:** Tungsten Halogen Quartz Bi-Pin STARLITE Low Pressure Clear Finish UV-Filter With Axial Filament GY6.35 Bi-Pin Base 75Watt 12Volt 4000Hr Lamp Life

#### Product Information

Abbrev. With Packaging Info.	75T4QCLAX 12V 40/CS 1/SKU
Approx. Lumens	1450
Average Rated Life (hr)	4000
Base	GY6.35 Bipin
Bulb	T12
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	0.472
Diameter (mm)	12.00
Ecologic	YES
Family Brand Name	STARLITE® Bi-Pin
Filament	AXIAL
Lamp Finish	Clear
Light Center Length - LCL (in)	1.125
Light Center Length - LCL (mm)	28.575
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	75.00

#### Footnotes

- Starlite Low Pressure - UV Filter Quartz
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.